




Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten.

General Information:
- Simplified representation, exemplary shown in gray.
- Document excluded from change process
- Units are in millimeters [mm] and degrees [°]
- Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2, PA plastic parts with about 2% (% by weight) moisture content.
- Workpiece zero point for mechanical processing
- Tolerances for mechanical processing
 milling contour to zero point ±0,2
 milling to milling contour ±0,1
- Machining radii min. R1, further on request
- Tolerances for printing DIN ISO 2768-m
- Web: www.phoenixcontact.com webcode: #1635

Additional Information:
A) PCB guidance
B) Marking area only for pad printing, other printing processes on request
C) Machining area
D) PCB, thickness= 1,6±0,2

Pos.	QTY	description	material
1	1	ICS20-F22S	PA
2	1	ICS20-F45S	PA
3	1	ICS20-F67S	PA
4	1	ICS20-F90S	PA

	DIN A2	document-No. / RI 01072519 / 03	date 07.04.2025	scale 2:1
	ident.-No. 1179830	document-type TECDOC 2D_Productdrawing		
page 1	of 1	description ICS20-F45S-1018		