


weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts gem. §18 UWG verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz (§19 UWG). Alle Rechte vorbehalten, insbesondere das Recht, Patent-, Gebrauchsmuster- oder Geschmacksmusteranmeldungen durchzuführen.


PHOENIX CONTACT Connector Technology GmbH
D-71083 Herrenberg

further information:

- see technical data M12-1
- see installation recommendation M16x1,5 design DSI



Pin layout



pin	colour	pin	colour
1	white/blue	5	white/green
2	white/brown	6	white/orange
3	brown	7	blue
4	orange	8	green

order-no.	L (m)	cable-printing
1238757	5,0	Art.-Nr. 1238757 5,0m 94B 4x2xAW G26 KW /JJ
1239505	10,0	Art.-Nr. 1239505 10,0m 94B 4x2xAW G26 KW /JJ

general tolerance acc. to DIN ISO 2768-c			technical changes reserved		Index 4 / 2016-09-06		scale: 3:2		
	date	name	description: Housing with crimp contacts Rear mounting (M16x1,5)					page: 1 of: 1	
design	2011-08-30	Thumm							
chk.									
			drawing-no.:		BAK-52MA38BX,XX (X,XX=L)		doc.-no.: 97011726		
			order-no.:		see chart				
			article designation:		VS-M12FSBP-0E-94B-LI/L (see chart)X				