


The copying, distribution and utilisation of this document as well as the communication of the contents to others without expressed authorization is prohibited according to §18 UWG German Law. Offenders will be held liable for the payment of damages according to §19 UWG German Law. All rights reserved, in particular the right to carry out patent, utility model or ornamental design registrations.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts gem §18 UWG verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz (§19 UWG). Alle Rechte vorbehalten, insbesondere das Recht, Patent-, Gebrauchsmuster- oder Geschmacksmusteranmeldungen durchzuführen.

CONINVERS GmbH Heisenbergstrasse 1 D-71083 Herrenberg


Mechanical data (according to IEC 61076-2-101)		Material	
no. of poles / coding	8 / A	housing / surface	GD-Zn / Ni
contact termination	crimp / pin	contact carrier	PA 66 / UL 94 V0
contact-Ø	0.8mm	colour	black
temperature range	-40 °C / +85 °C	cable	970
protection class	IP 67	cross section	1x2xAWG22/2x2xAWG26
mating cycles	> 100	contacts / surface	CuZn / Au
locking system	M12 STANDARD / SPEEDCON	sealing gasket	FKM
		potting	PU 2k / UL 94 V0

further information:
- see technical data M12-1
- see installation recommendation M16x1,5 design DSI



All specified data refers to the mounted M12 installation plugs >IP54 and requires that the connector pair is correctly plugged and locked. Influences from wires, cables or PCB mounting are also to be taken into consideration.

View of pin assignment
Plug-in side



Pin layout

pin	colour	pin	colour
1	n.c.	5	green/white
2	orange/white	6	blue
3	orange	7	brown
4	n.c.	8	green

order-no.	L (m)
1239591	0.5
1239592	1.0
1239593	2.0
1239594	5.0

general tolerance acc. to DIN ISO 2768-c			technical changes reserved		Index 2 / 2014-06-04		scale: 3:2				
date			name			description: Housing with crimp contacts Rear mounting (M16x1,5)					
design			2011-08-29								
chk.											
						page: 1 of: 1					
			drawing-no.:		BAK-50M037AX,XX (X,XX=L)		doc.-no.:		97012216		
			order-no.:		see chart						
			article designation:		SACCBP-M12MS-6CON-M16/L (see chart) -970X						