


The copying, distribution and utilisation of this document as well as the communication of the contents to others without expressed authorization is prohibited according to §18 UWG German Law. Offenders will be held liable for the payment of damages according to §19 UWG German Law. All rights reserved, in particular the right to carry out patent, utility model or ornamental design registrations.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts gem §18 UWG verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz (§19 UWG). Alle Rechte vorbehalten, insbesondere das Recht, Patent-, Gebrauchsmuster- oder Geschmacksmusteranmeldungen durchzuführen.

CONINVERS GmbH Heisenbergstrasse 1 D-71083 Herrenberg


Mechanical data (according to IEC 61076-2-101)		Material	
no. of poles / coding	5 / A	housing / surface	GD-Zn / Ni
contact termination	crimp / pin	contact carrier	PA 66 / UL 94 V0
contact-Ø	1mm	colour	purple
temperature range	-40 °C / +85 °C	cable	920
protection class	IP 67	cross section	1x2xAWG24/1x2xAWG22
mating cycles	> 100	contacts / surface	CuZn / Au
locking system	M12 STANDARD / SPEEDCON	sealing gasket	NBR
		potting	PU 2k / UL 94 V0

further information:
- see technical data M12-1
- see installation recommendation M16x1,5 design EC



All specified data refers to the mounted M12 installation plugs ≥ IP54 and requires that the connector pair be correctly plugged and locked. Influences from wires, cables or PCB mounting are also to be taken into consideration.

View of pin assignment
Plug-in side



Pin layout

pin	colour	cross section
1	shield (Drain)	-
2	red (V+)	AWG22
3	black (V-)	AWG22
4	white (CAN_H)	AWG24
5	blue (CAN_L)	AWG24

order-no.	L (m)	cable printing
1239889	0.5	Art.-Nr. 1239889 0.5m 920 1x2xAWG24 / 1x2xAWG22 KW / JJ
1239890	1.0	Art.-Nr. 1239890 1.0m 920 1x2xAWG24 / 1x2xAWG22 KW / JJ
1239891	2.0	Art.-Nr. 1239891 2.0m 920 1x2xAWG24 / 1x2xAWG22 KW / JJ
1239892	5.0	Art.-Nr. 1239892 5.0m 920 1x2xAWG24 / 1x2xAWG22 KW / JJ
1525665	10.0	Art.-Nr. 1525665 10.0m 920 1x2xAWG24 / 1x2xAWG22 KW / JJ

general tolerance acc. to DIN ISO 2768-c			technical changes reserved		Index 1 / 2011-08-25	scale: 3:2	
	date	name	description: Housing with crimp contacts Front mounting (M16x1,5)			page: 1 of: 1	
design	2011-08-25	Thumm					
chk.							
			drawing-no.:	BAK-3NQ220BX,XX (X,XX=L)			
			order-no.:	see chart			
			article designation:	SACCEC-M12MS-5CON-M16/L (see chart) -920X			