

A


B

Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations.


Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten.

UM-BASIC-KIT-B72-L....

Assembly example UM-BASIC-KIT-B72-L200



Assembly example (UM-BASIC-KIT-B72-L200)



A

B


C

D

E

F

Profile





article	prolife length PL	modul length ML
UM-BASIC-KIT-B...-L60	(43,8)	(63,8)
UM-BASIC-KIT-B...-L80	(63,8)	(83,8)
UM-BASIC-KIT-B...-L100	(83,8)	(103,8)
UM-BASIC-KIT-B...-L120	(103,8)	(123,8)
UM-BASIC-KIT-B...-L150	(133,8)	(153,8)
UM-BASIC-KIT-B...-L180	(163,8)	(183,8)
UM-BASIC-KIT-B...-L200	(183,8)	(203,8)
UM-BASIC-KIT-B...-L250	(233,8)	(253,8)


- General Information:
- Simplified representation.
 - Document excluded from change process
 - Units are in millimeters [mm] and degrees [°]
 - Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2, PA plastic parts with about 2% (% by weight) moisture content.
 - Web: www.phoenixcontact.com webcode: #0314
 - PCB configurator web: www.phoenixcontact.com webcode: #0512

KIT (not mounted)					
Pos.	QTY	Description	Material		
1	1	UM-BASIC PROFIL	PVC		
2	1	SIDE ELEMENT LEFT	PA		
3	1	SIDE ELEMENT RIGHT	PA		
 DIN A2		document-No. / RI 01370101 / 00	date 02.08.2021	scale 1:1	
		ident.-No. 1300348	document-type TECDOC 2D_Productdrawing		
		description UM-BASIC-KIT-B72-L150-7035			
		page 1 of 6			

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten.



- Recommended PCB-outline see further documentation

Pos.	QTY	description		material	
1	1	PROFILE		PVC	
 DIN A3		document-No. / RI 01370101 / 00		date 02.08.2021	scale 1:1
		ident.-No. 1300348	document-type TECDOC 2D_Productdrawing		
		description UM-BASIC-KIT-B72-L150-7035			
page 2		of 6			


A

A



Recommended PCB for: UM-PRO 72 and UM-BASIC 72

B

B




Detail1




Detail1

2:1



General Information:

- Simplified representation
- Document excluded from change process
- Linear dimensions [mm]
- Web: www.phoenixcontact.com webcode: #0314 / #0313
- General tolerances for PCB: dimensions ≤ 30 : $\pm 0,1/R \pm 0,2/\pm 1^\circ$
dimensions > 30 : $\pm 0,15/R \pm 0,2/\pm 1^\circ$
symmetry: 0,2
-  Restricted area, no components
-  Restricted area, optional

Additional Information:

- A) Optional drilling hole, restricted area and recommended Sn-plated pad for UM-PRO PE CONTACT L1
- B) Optional cutout and restricted area for UM-PRO PCB S-LOCK
- C) Optional cutout and restricted area for UM-PRO PCB C-LOCK L1
- X: PCB length (profile length=X-16,2 ; module length=X+3,8)
- Y: Position of optional cutouts with restricted areas ; Range: Y=8,6...(X-8,6)


D

E

F

Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten.

 DIN A2	document-No. / RI 01370101 / 00	date 02.08.2021	scale 1:1
	ident.-No. 1300348	document-type TECDOC 2D_Productdrawing	
page 3 of 6	description UM-BASIC-KIT-B72-L150-7035		

1

2

3


4

5

6

7

8



Additional Information:

A) optional drilling hole, restricted area and recommended Sn-plated pad for UM-PRO PE CONTACT L2/L3

B) optional cutout and restricted area for UM-PRO PCB S-LOCK




C) optional cutout and restricted area for UM-PRO PCB C-LOCK L2/L3

X: PCB length (profile length=x-16,2 ; module length=x+3,8)


Y: Position of optional cutouts with restricted areas ; Range: y=8,6...(x-8,6)

Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten.



height
depth
width/length




General Information:

- Simplified representation
- Document excluded from change process
- Linear dimensions [mm]
- Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2, PA plastic parts with about 2% (% by weight) moisture content.
- Workpiece zero point for mechanical processing
- Tolerances for mechanical processing are ISO 2768-mK
- Machining radii min. R1, further on request
- Web: www.phoenixcontact.com webcode: #0313 / #0314


Additional Information:

A) PCB L1
B) PCB L2
C) PCB L3
D) Mounting rail according to DIN EN 60715: TH 35-7,5 or Mounting rail similar to DIN EN 60715: TH 35-15x1,5
E) Fix point for UM-PRO PE CONTACT
F) Fix point for UM-PRO 72 PROFILE
G) Fix point for UM-PRO MOUNT
H) Marking area

- Recommended PCB-outline see further documentation

Pos.	QTY	description		material	
1	1	LATERAL ELEMENT LEFT		PA	
 DIN A3		document-No. / RI 01370101 / 00		date 02.08.2021	scale 2:1
		ident.-No. 1300348	document-type TECDOC 2D_Productdrawing		
		description UM-BASIC-KIT-B72-L150-7035			
		page 5 of 6			


Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten.



- Simplified representation
- Document excluded from change process
- Linear dimensions [mm]
- Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2, PA plastic parts with about 2% (% by weight) moisture content.
-  Workpiece zero point for mechanical processing
- Tolerances for mechanical processing are ISO 2768-mK
- Machining radii min. R1, further on request
- Web: www.phoenixcontact.com webcode: #0313 / #0314

- A) PCB L1
- B) PCB L2
- C) PCB L3
- D) Mounting rail according to DIN EN 60715: TH 35-7,5 or
Mounting rail similar to DIN EN 60715: TH 35-15x1,5
- E) Fix point for UM-PRO PE CONTACT
- F) Fix point for UM-PRO 72 PROFILE
- G) Fix point for UM-PRO MOUNT
- H) Marking area

- Recommended PCB-outline see further documentation

Pos.	QTY	Description	Material
1	1	LATERAL ELEMENT RIGHT	PA
 DIN A3		document-No. / RI 01370101 / 00	date 02.08.2021 scale 2:1
		ident.-No. 1300348	document-type TECDOC 2D_Productdrawing
page 6 of 6		description UM-BASIC-KIT-B72-L150-7035	