

A


B

Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations.


Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten.

UM-BASIC-KIT-B122-L....

Assembly example UM-BASIC-KIT-B122-L200




Profile



- General Information:
- Simplified representation.
 - Document excluded from change process
 - Units are in millimeters [mm] and degrees [°]
 - Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2, PA plastic parts with about 2% (% by weight) moisture content.
 - Web: www.phoenixcontact.com webcode: #0314
 - PCB configurator web: www.phoenixcontact.com webcode:#0512

Assembly example

(UM-BASIC-KIT-B122-L200)









article	prolife length		modul length	
	PL		ML	
UM-BASIC-KIT-B...-L60	(43,8)		(63,8)	
UM-BASIC-KIT-B...-L80	(63,8)		(83,8)	
UM-BASIC-KIT-B...-L100	(83,8)		(103,8)	
UM-BASIC-KIT-B...-L120	(103,8)		(123,8)	
UM-BASIC-KIT-B...-L150	(133,8)		(153,8)	
UM-BASIC-KIT-B...-L180	(163,8)		(183,8)	
UM-BASIC-KIT-B...-L200	(183,8)		(203,8)	
UM-BASIC-KIT-B...-L250	(233,8)		(253,8)	

KIT (not mounted)					
Pos.	QTY	Description	Material		
1	1	UM-BASIC PROFIL	PVC		
2	1	SIDE ELEMENT LEFT	PA		
3	1	SIDE ELEMENT RIGHT	PA		
 DIN A2		document-No. / RI	date	scale	
		01370764 / 00	02.08.2021	1:1	
		ident.-No.	document-type		
		1300364	TECDOC 2D_Productdrawing		
page 1 of 6		description			
UM-BASIC-KIT-B122-L150-7035					

F

Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten.




General Information

- Simplified representation
- Document excluded from change process
- Linear dimensions [mm]
- Tolerances, apply in a normal climate according to DIN EN ISO 291-23/50-2,
- Web: www.phoenixcontact.com webcode: #0313




Additional Information:

- A) PCB L1
- B) PCB L2
- C) PCB L3
- D) Groove to fix the lateral element, UM-PRO COVER L/R
- E) Length of profile according to customer specification.
Profil length min. 30mm up to max. 1000mm
- F) Fixing for optional PCB S-LOCK
- G) Fixing for optional PCB C-LOCK L ...
- H) Area for optional marking strip SK 5,0...

- Recommended PCB-outline see further documentation


Pos.	QTY	description		material	
1	1	PROFILE		PVC	
 DIN A3		document-No. / RI		date	scale
		01370764 / 00		02.08.2021	1:1
		ident.-No.	document-type		
		1300364	TECDOC 2D_Productdrawing		
page 2 of 6		description			
		UM-BASIC-KIT-B122-L150-7035			

Recommended PCB for: UM-PRO 122 and UM-BASIC 122



Detail1

Detail1





General Information:

- Simplified representation
- Document excluded from change process
- Linear dimensions [mm]
- Web: www.phoenixcontact.com webcode: #0314 / #0313

Addition Information

- General tolerances for PCB: dimensions ≤ 30 : $\pm 0,1/R \pm 0,2/\pm 1^\circ$
dimensions > 30 : $\pm 0,15/R \pm 0,2/\pm 1^\circ$
symmetry: 0,2




-  Restricted area, no components
-  Restricted area, optional

Additional Information:

- A) Optional drilling hole, restricted area and recommended Sn-plated pad for UM-PRO PE CONTACT L1
- B) Optional cutout and restricted area for UM-PRO PCB S-LOCK
- C) Optional cutout and restricted area for UM-PRO PCB C-LOCK L1
- X: PCB length (profile length=X-16,2 ; module length=X+3,8)
- Y: Position of optional cutouts with restricted areas ; Range: Y=8,6...(X-8,6)

 DIN A2	document-No. / RI 01370764 / 00	date 02.08.2021	scale 1:1
	ident.-No. 1300364	document-type TECDOC 2D_Productdrawing	
page 3 of 6	description UM-BASIC-KIT-B122-L150-7035		


Recommended PCB for: UM-PRO 122 and UM-BASIC 122



General Information:

- Simplified representation
- Document excluded from change process
- Linear dimensions [mm]
- Web: www.phoenixcontact.com webcode: #0313 / #0314

Addition Information

- General tolerances for PCB: dimensions ≤ 30 : $\pm 0,1/R \pm 0,2/\pm 1^\circ$
dimensions > 30 : $\pm 0,15/R \pm 0,2/\pm 1^\circ$
symmetry: 0,2
-  Restricted area, no components
-  Restricted area, optional

Additional Information:

A) optional drilling hole, restricted area and recommended Sn-plated pad for UM-PRO PE CONTACT L2/L3


B) optional cutout and restricted area for UM-PRO PCB S-LOCK

C) optional cutout and restricted area for UM-PRO PCB C-LOCK L2/L3

X: PCB length (profile length= $x-16,2$; module length= $x+3,8$)

Y: Position of optional cutouts with restricted areas ; Range: $y=8,6 \dots (x-8,6)$

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten.



Pos.	QTY	description		material
1	1	LATERAL ELEMENT LEFT		PA
 DIN A2		document-No. / RI 01370764 / 00	date 02.08.2021	scale 2:1
		ident.-No. 1300364	document-type TECDOC 2D_Productdrawing	
page 5 of 6		description UM-BASIC-KIT-B122-L150-7035		

