



Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten.



- Exemplary shown in gray
- Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2, PA plastic parts with about 2% (% by weight) moisture content.
- When using this connection technology in housing systems from Phoenix Contact see the appropriate documentation
-  Restricted area, no components, no solder mask
- Tolerances for PCB, dimensions ≤ 30 : $+/-0,10$ / $R+/-0,2$ / $+/-1^\circ$
symmetry: 0,2 dimensions > 30 : $+/-0,15$ / $R+/-0,2$ / $+/-1^\circ$
- Undimensioned PCB radii $R=1,2$
- Web: www.phoenixcontact.com

- A. Main PCB $t=1,6\pm0,2$
- B. Second PCB $t=1,6\pm0,2$
- C. PCB top side
- D. PCB top side (dimensioning of restricted area)
- E. Dimension for PCB edge: ICC connection technology and ICS Filler
- F. Dimension for PCB edge: ICS housing
- G. Primary marking area
- H. Secondary marking area



 DIN A3		document-no. / ri 01581196 / 03		article-no. 1380319		scale 2:1		- Simplified representation - Document excluded from change process - Linear dimensions [mm]	
		date 22.04.2025		document-type TECDOC 2D_Productdrawing					
page 1 of 1		description ICC20-TS2,5/3R5,0-1018							