

[illegible]

Transfer or duplication in communication of its content is granted. Violations given in case of patent, utility or tolerance specifications

1

2

MOUNTING CLAMP

$\varnothing (60-140)$

B

3

SCREW

(10)

1:1

C

4 5 6 7 8

Application example
(OCS HP 121006 ... with OCS POLEFIX 1210)

General Information:

- Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2
- Web: www.phoenixcontact.com webcode: #3249

Additional Information:

A. Accessories for:
OCS HP 121006 GY7035 and OCS HP 121006 TRANS

B. Screw drive (SW 10mm, slot width 1.6mm)

C. Screwdriver recommendation SF-PH 1-80

KIT (not mounted)			
Pos.	QTY	Description	Material
1	2	POLEFIX PLATE	STL
2	2	POLEFIX CLAMP	STL
3	4	SCREW	SSTL

DIN A2 	document-no. / ri 01505577 / 01	article-no. 1476926	scale 1:2	- Simplified representation - Document excluded from change process - Linear dimensions [mm]
	date 03.07.2025	document-type		
	description			
page 1	of 1	OCS POLEFIX 1210		

Technical drawing of the HP 10000 series handle assembly, showing a side view and a top view.

The side view shows a handle with a grip and a mounting bracket. The grip is labeled with a diameter of $\varnothing(60-140)$. The mounting bracket is shown in two positions: one with the handle in the open position and one with the handle in the closed position.

The top view shows the handle's profile and the mounting bracket's attachment points. The handle is labeled with a length of 100 mm. The mounting bracket is shown in two positions: one with the handle in the open position and one with the handle in the closed position.

KIT (not mounted)			
Pos.	QTY	Description	Material
1	2	POLEFIX PLATE	STL
2	2	POLEFIX CLAMP	STL
3	4	SCREW	SSTL

 DIN A2		document-no. / ri 01505577 / 01		article-no. 1476926		scale 1:2		- Simplified representation - Document excluded from change process	
 PHOENIX CONTACT		date 03.07.2025		document-type		- Linear dimensions (mm)			
page 1 of 1		description		OCS POLEFIX 1210					