







Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Bauartbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.






LID swivel



Example:

max. lid opening



General Information:

- Simplified representation, exemplary shown in gray.
- Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2, PA plastic parts with about 1,7% (% by weight) moisture content.
- Workpiece zero point for mechanical processing
- Tolerances for printing DIN ISO 2768-m
- Web: www.phoenixcontact.com

Additional Information:

- A. Marking area
- B. Housing
- C. Hinge

KIT (not mounted)			
Pos.	QTY	Description	Material
1	1	COVER	PA GF
2	1	LID	PC

 DIN A2		document-no. / n° 01640739 / 00		article-no. 1524431		scale 1:1		- Simplified representation - Document excluded from change process - Linear dimensions [mm]
		date 26.04.2024		document-type TECDOC 2D_Productdrawing				
page 1		of 1		description		MCS-112X90-C-S-1018		