



Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Bauteilbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.

Recommended panel cutout



Phoenix Logo


Lasered 2,6 mm H

Phoenix Part Number


1 mm H

Date Code

1 mm H



PCB drill hole dimensions (see from component side)




Recommended PCB Layout

Tol: ±0,05 mm

T=1,60±0,15 mm



Detail1

5:1



Detail2

5:1



Detail1

15,75

Detail3

8,5


LED 1
GREEN

LED 2
YELLOW

Detail2

Detail3

5:1



Detail4

5:1

LED 1
GREEN
P11
P12

LED 2
YELLOW
P13
P14

LED-Specifications

LED	Forward Voltage (max)	*Forward Voltage (Typical)
GREEN	2,4 V	2,2 V
YELLOW	2,5 V	2,1 V

*Forward DC current: 20 mA

General Tolerances

1 Decimal Place	±0,25
2 Decimal Places	±0,20
3 Decimal Places	±0,15

DIN A3



page 1 of 2

document-no. / ri
01741028 / 00

article-no.
1663962

date
07.11.2024

document-type
TECDOC 2D_Productfamily

description
CUC-IB4M-J1ST-AT/R4T-L1


scale
2:1

- Simplified representation
- Document excluded
from change process
- Linear dimensions [mm]

Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Bauartbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.

PCB SIDE



JACK SIDE

ELECTRONICAL SPECIFICATIONS

1. ACCORDING TO IEEE 802.3
2. TURN RATIO @100KHz: (P1~P2):(J1~J2) = 1:1±5%
(P3~P6):(J3~J6) = 1:1±5%
3. PRIMARY INDUCTANCE: 350µH MIN @100KHz
0,1V 8mA DC BIAS
4. DC RESISTANCE: 1,2 OHMS MAX
5. INSERTION LOSS: 1-100MHz -1,2dB MAX
6. RETURN LOSS: 1-30MHz -16dB MIN
30-60MHz -12dB MIN
60-80MHz -10dB MIN
7. CROSS TALK: 1-100MHz -30dB MIN
8. COMMON TO COMMON
MODE ATTENUATION: 1-100MHz -30dB MIN
9. ISOLATION: PHY SIDE TO LINE SIDE: 1500VAC or 2250VDC

- EN ISO 291 23/50

 DIN A3		document-no. / ri 01741028 / 00		article-no. 1663962		scale 2:1		- Simplified representation - Document excluded from change process - Linear dimensions [mm]
		date 07.11.2024		document-type TECDOC 2D_Productfamily				
		description						
		CUC-IB4M-J1ST-AT/R4T-L1						
page 2		of 2						