



Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts, sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten.

Bearbeitungsbedingungen: Das Spiel ist in den Toleranzangaben nicht berücksichtigt.

PCB drill hole dimensions (see from component side)



PCB thickness: 1,6mm



*Forward DC current: 20 mA


General Tolerances	 DIN A3	document-no. / ri 01761537 / 01	article-no. 1663978	scale 2:1	- Simplified representation - Document excluded from change process - Linear dimensions [mm]
1 Decimal Place ±0,25		date 12.12.2024	document-type TECDOC 2D_Productfamily		
2 Decimal Places ±0,20		description CUC-IC4M-J1ST-S/R4T-L1			
3 Decimal Places ±0,15	page 1	of 2			

CUC-IC4M-J1ST-S/R4T-L1

Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Bauartbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.

PCB SIDE



JACK SIDE

ELECTRONICAL SPECIFICATIONS

1. ACCORDING TO IEEE 802.3
2. TURN RATIO @100KHz: (P1~P2):(J1~J2) = 1:1±5%
(P7~P8):(J3~J6) = 1:1±5%
3. PRIMARY INDUCTANCE: 350μH MIN @100KHz
0,1V 8mA DC BIAS
4. DC RESISTANCE: 1,2 OHMS MAX
5. INSERTION LOSS: 1-100MHz -1,0dB MAX
6. RETURN LOSS: 1-30MHz -16dB MIN
30-60MHz -12dB MIN
60-80MHz -10dB MIN
7. CROSS TALK: 1-100MHz -30dB MIN
8. COMMON TO COMMON MODE ATTENUATION: 1-100MHz -30dB MIN
9. ISOLATION: PHY SIDE TO LINE SIDE: 1500VAC or 2250VDC

- EN ISO 291 23/50

 DIN A3		document-no. / ri 01761537 / 01	article-no. 1663978	scale 2:1	- Simplified representation - Document excluded from change process - Linear dimensions [mm]
		date 12.12.2024	document-type TECDOC 2D_Productfamily		
		description CUC-IC4M-J1ST-S/R4T-L1			
page 2	of 2				