


Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Bauteilbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.

Recommended panel cutout



Phoenix Logo


Lasered 2,6 mm H

Phoenix Part Number


1 mm H

Date Code

1 mm H




PCB drill hole dimensions (see from component side)



Recommended PCB Layout

Tol: $\pm 0,05$ mm

T=1,60 $\pm 0,15$ mm



Detail1

15,75

Detail3

8,5



LED 1
GREEN

LED 2
YELLOW

Detail2


Detail3

5:1




Detail1

5:1



Detail2

5:1



Detail4

5:1

LED 1
GREEN
P11
P12

LED 2
YELLOW
P13
P14


LED-Specifications		
LED	Forward Voltage (max)	*Forward Voltage (Typical)
GREEN	2,4 V	2,2 V
YELLOW	2,5 V	2,1 V

*Forward DC current: 20 mA

General Tolerances		DIN A3		document-no. / ri	article-no.	scale	- Simplified representation - Document excluded from change process - Linear dimensions [mm]
1 Decimal Place	$\pm 0,25$	PHENIX CONTACT		date	document-type	2:1	
2 Decimal Places	$\pm 0,20$			07.11.2024	TECDOC 2D_Productfamily		
3 Decimal Places	$\pm 0,15$	page 1	of 2	description			CUC-IB7G-J1ST-AT/R4R-L1

Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Bauartbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.



ELECTRONICAL SPECIFICATIONS

1. ACCORDING TO IEEE 802.3

2. TURN RATIO @100KHz: (P10~P9):(J1~J2) = 1:1±5%
(P8~P7):(J3~J6) = 1:1±5%
(P4~P3):(J4~J5) = 1:1±5%
(P2~P1):(J7~J8) = 1:1±5%

3. PRIMARY INDUCTANCE: 350μH MIN @100KHz
0,1V 8mA DC BIAS

4. DC RESISTANCE: 1,2 OHMS MAX

5. INSERTION LOSS: 1-125MHz -1,0dB TYP

6. RETURN LOSS: 1-40MHz -16dB MIN
40-60MHz -12dB MIN
60-80MHz -10dB MIN
80-100MHz -8dB MIN

7. CROSS TALK: 1-100MHz -30dB MIN

8. COMMON TO COMMON
MODE ATTENUATION: 1-100MHz -30dB MIN

9. ISOLATION: PHY SIDE TO LINE SIDE: 2250VDC

- EN ISO 291 23/50

 DIN A3		document-no. / ri 01760859 / 00		article-no. 1663986		scale 2:1		- Simplified representation - Document excluded from change process - Linear dimensions [mm]
		date 07.11.2024		document-type TECDOC 2D_Productfamily				
page 2 of 2		description CUC-IB7G-J1ST-AT/R4R-L1						