


Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Bauartbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.

Recommended panel cutout



Phoenix Logo


Lasered 2,6 mm H

Phoenix Part Number


1 mm H

Date Code

1 mm H




PCB drill hole dimensions (see from component side)



Recommended PCB Layout

Tol: $\pm 0,05$ mm

T=1,60 $\pm 0,15$ mm




Detail1

5:1

Detail1

5:1



Detail2

5:1

Detail3


LED 1
GREEN

LED 2
YELLOW

Detail2

Detail3


5:1




Detail4

5:1

LED 1
GREEN



LED 2
YELLOW



LED-Specifications

LED	Forward Voltage (max)	*Forward Voltage (Typical)
GREEN	2,4 V	2,2 V
YELLOW	2,5 V	2,1 V

*Forward DC current: 20 mA

General Tolerances

1 Decimal Place	$\pm 0,25$
2 Decimal Places	$\pm 0,20$
3 Decimal Places	$\pm 0,15$

DIN A3



page 1 of 2

document-no. / ri
01760892 / 00

article-no.
1663996

date
07.11.2024

document-type
TECDOC 2D_Productfamily


description
CUC-IB2G-J1ST-AT/R4R-PL1

scale
2:1

- Simplified representation
- Document excluded
from change process
- Linear dimensions [mm]

PCB SIDE

JACK SIDE



ELECTRONICAL SPECIFICATIONS

1. ACCORDING TO IEEE 802.3
2. TURN RATIO @100KHz: (P2~P3):(J1~J2) = 1:1±5%
(P4~P5):(J3~J6) = 1:1±5%
(P6~P7):(J4~J5) = 1:1±5%
(P8~P9):(J7~J8) = 1:1±5%
3. PRIMARY INDUCTANCE: 350µH MIN @100KHz
0,1V 8mA DC BIAS
4. DC RESISTANCE: 1,2 OHMS MAX
5. INSERTION LOSS: 1-100MHz -1,0dB MAX
100-125MHz -1,2dB MAX
6. RETURN LOSS: 1-40MHz -16dB MIN
40-60MHz -12dB MIN
60-80MHz -10dB MIN
80-100MHz -8dB MIN
7. CROSS TALK: 1-100MHz -30dB MIN
8. COMMON TO COMMON MODE ATTENUATION: 1-100MHz -30dB MIN
9. ISOLATION: PHY SIDE TO LINE SIDE: 2250VDC

						00	date	name	ident.-No. / RI	material	scale	dim.var.
						creat.	24.10.24	pbkp11	1663996 / 00	-	2:1	
						check.	07.11.24	il259h	SAP change-No. NAB210064E04	part-rev.		
								DIN A3	document-type	document-No.	surface in µm	
								PHENIX CONTACT	TECDOC 2D_Productfamily	01760892		
									description			
RI	date	revision		name	check.on	name	page 2	of 2	CUC-IB2G-J1ST-AT/R4R-PL1			