




Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Baugrößtbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.

Recomended panel cutout




PCB drill hole dimensions (see from component side)




Recommended PCB Layout (Tol: ±0,05, T=1,60±0,15mm)


PCB thickness: 1,6mm



LED 1
YELLOW



LED 2
GREEN



Detail4
5:1

LED-Specifications		
LED	Forward Voltage (max)	*Forward Voltage (Typical)
GREEN	2,4 V	2,2 V
YELLOW	2,5 V	2,1 V

*Forward DC current: 20 mA

General Tolerances

1 Decimal Place	±0,25
2 Decimal Places	±0,20
3 Decimal Places	±0,15



page 1 of 2

document-no. / ri
01724960 / 02 1664048

date
12.12.2024

document-type
TECDOC 2D_Productfamily

description
CUC-IC2G-J1ST-S/R4T-L1


scale
2:1

- Simplified representation
- Document excluded
from change process
- Linear dimensions [mm]

Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Bauartbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.

PCB SIDE




JACK SIDE

ELECTRONICAL SPECIFICATIONS

1. ACCORDING TO IEEE 802.3
2. TURN RATIO @100KHz: (P2~P3):(J1~J2) = 1:1±5%
(P4~P5):(J3~J6) = 1:1±5%
(P6~P7):(J4~J5) = 1:1±5%
(P8~P9):(J7~J8) = 1:1±5%
3. PRIMARY INDUCTANCE: 350μH MIN @100KHz,0.1V 8mA DC BIAS
4. DC RESISTANCE 1.2 OHMS MAX
5. INSERTION LOSS: 1-100MHz -1.0dB MAX
100-125MHz -1.2dB MAX
6. RETURN LOSS: 1-40MHz -16dB MIN
40-60MHz -12dB MIN
60-80MHz -10dB MIN
80-100MHz -8dB MIN
7. CROSS TALK: 1-100MHz -30dB MIN
8. COMMON TO COMMON MODE ATTENUATION: 1-100MHz -30dB MIN
9. ISOLATION: PHY SIDE TO LINE SIDE: 2250VDC

- EN ISO 291 23/50

 DIN A3		document-no. / ri 01724960 / 02	article-no. 1664048	scale 2:1	- Simplified representation - Document excluded from change process - Linear dimensions [mm]
		date 12.12.2024	document-type TECDOC 2D_Productfamily		
		description CUC-IC2G-J1ST-S/R4T-L1			
page 2	of 2				