


Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadensersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Bauteilbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.

Recommended panel cutout



Phoenix Logo


Lasered 2,6 mm H

Phoenix Part Number

1 mm H


Date Code

1 mm H




Panel

PCB




PCB drill hole dimensions (see from component side)



Recommended PCB Layout


Tol: $\pm 0,05$ mm

T=1,60 $\pm 0,15$ mm



Detail1

Detail3




LED 1
GREEN

LED 2
YELLOW


Detail1

5:1




Detail2

5:1



Detail3

5:1



Detail4

5:1

LED 1
GREEN
P11 $\rightarrow$ P12

LED 2
YELLOW
P13 $\rightarrow$ P14

LED-Specifications

LED	Forward Voltage (max)	*Forward Voltage (Typical)
GREEN	2,4 V	2,2 V
YELLOW	2,5 V	2,1 V

*Forward DC current: 20 mA

General Tolerances

1 Decimal Place	$\pm 0,25$
2 Decimal Places	$\pm 0,20$
3 Decimal Places	$\pm 0,15$

DIN A3



page 1 of 2

document-no. / ri
01758869 / 00 1664067

date
04.11.2024

document-type
TECDOC 2D_Productfamily


description
CUC-IA5M-J1ST-AB/R4T-L1

scale
2:1

- Simplified representation
- Document excluded from change process
- Linear dimensions [mm]

PCB SIDE

JACK SIDE



ELECTRONICAL SPECIFICATIONS

1. ACCORDING TO IEEE 802.3
2. TURN RATIO @100KHz: (P1~P2):(J1~J2) = 1:1±5%
(P3~P6):(J3~J6) = 1:1±5%
3. PRIMARY INDUCTANCE: 350µH MIN @100KHz
0,1V 8mA DC BIAS
4. DC RESISTANCE: 1,2 OHMS MAX
5. INSERTION LOSS: 1-100MHz -1,2dB MAX
6. RETURN LOSS: 1-30MHz -16dB MIN
30-60MHz -12dB MIN
60-80MHz -10dB MIN
7. CROSS TALK: 1-100MHz -30dB MIN
8. COMMON TO COMMON
MODE ATTENUATION: 1-100MHz -30dB MIN
9. ISOLATION: PHY SIDE TO LINE SIDE: 1500VAC or 2250VDC

						00	date	name	ident.-No. / RI	material	scale	dim.var.
						creat.	17.10.24	pbkp11	1664067 / 00	-	2:1	
						check.	04.11.24	il259h	SAP change-No. NAB210064E04	part-rev.		
								DIN A3	document-type	document-No.	surface in µm	
								PHENIX CONTACT	TECDOC 2D_Productfamily	01758869		
									description			
RI	date	revision	name	check.on	name	page 2	of 2					CUC-IA5M-J1ST-AB/R4T-L1