

HOUSING LOWER PART

Top view: 71,6^{+0,3}_{-0,18} (4units), 13,8 ±0,08, 89,7^{+0,3}_{-0,24}

Side view: 17,2 ±0,08, 12,1 ±0,08, 7 ±0,07, 24,6 ±0,095, 7,1 ±0,07, 16,4 ±0,08, 1,8

Cross-section A-A: 42,9 ±0,12, 37,8 ±0,12, 36,2 ±0,12, 34,9 ±0,12, 32,35 ±0,12, 27,3 ±0,095, 22,25 ±0,095

Assembly example

Overall dimensions complaint DIN 43880

Partial view A-A: 6 ±0,12, 43,8 ±0,2, 54,7^{+0,3}_{-0,35}, 4,5 ±0,12

Partial view B-B 2:1: 7,2, 7,1 ±0,07, 16,4 ±0,08, 1,8

FOOT CATCH

Top view: 14,4 ±0,13, 4,2 ±0,095

Side view: 5,9 ±0,095, 29,8 ±0,15

WALL MOUNTING

Top view: 105,2 ±0,38, 99 ±0,38, 35,8 ±0,18, 4,2 ±0,095, 2, 1, for screws max. Ø4

General Information:

- Simplified representation
- Document excluded from change process
- Units are in millimeters [mm] and degrees [°]
- Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2,
- Web: www.phoenixcontact.com webcode: #0311

Additional Information:

A. PCB fixing

B. HBUS connector

C. PCB 1 (main PCB)

D. Housing upper part

E. Cover

F. Mounting rail like EN 60715: TH 35-7,5 or mounting rail TH 35-15x1,5 similar to EN 60715

G. Plug for HBUS, (PSTD 0,65x0,65/9-2,54)

H. Position PCB 9 or position plate

HOUSING LOWER PART with FOOT CATCH mounted

Top view: 1, 2