

Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Bauartbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.

1







2

3


4

5

6



view X



5:1



A
position 1

A
position 2

Pos.	QTY	Description	Material
1	1	HOUSING	PA
2	1	COVER	PA
3	5	SPRING OPENER	PBT
4	2	CODING-PLUG	PA
5	2	CODING-HEADER	PA
6	5	PUSH-IN-CONTACT	Cu alloy, STL

General Information:


- Corresponding header ICC25-H/5L/R3,5
- Simplified representation, exemplary shown in gray
- Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2, PA plastic parts with about 2% (% by weight) moisture content.
- Web: www.phoenixcontact.com

Additional Information:


- A. Marking area
- Printing method: pad printing
 - Printing color: black similar RAL9005
- B. Contact type

schematic symbol	description	electrical symbol
	single contact	
	without contact	


C) Coding adjustment with screwdriver
e.g. 1205037 - SZS 0,4X2,5 VDE




A



B



C



D

Example: ICC25-PPC1,5/5-3,5- CB

position 1

position 2

	DIN A3	document-no. / ri	01787708 / 00	article-no.	1813771	scale	2:1	- Simplified representation - Document excluded from change process - Linear dimensions [mm]
	PHOENIX CONTACT	date	18.02.2025	document-type	TECDOC 2D_Productdrawing			
page 1	of 1	description ICC25-PPC1,5/5-3,5-AA-BK TP1-5						

1

2

3

4

5

6