




HOUSING LEFT




HOUSING RIGHT





Assembly example: ME MAX 90 3-3




HOUSING MIDDLE




FRONT PLATE




1:2




1:2




HINGED COVER



FOOT CATCH



SPRING



KIT (not mounted)			
Pos.	QTY	Description	Material
1	1	HOUSING LEFT	PA
2	1	HOUSING RIGHT	PA
3	3	HOUSING MIDDLE	PA
4	1	FRONT PLATE	PA
5	1	HINGED COVER	PC
6	1	FOOT CATCH	STL
7	1	SPRING	STL

General Information:
- Simplified representation, exemplary shown in gray.
- Document excluded from change process
- Units are in millimeters [mm] and degrees [°]
- Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2.
- PA plastic parts with about 2% (% by weight) moisture content.
- Workpiece zero point for mechanical processing
- Tolerances for mechanical processing are ISO 2768-mk
- Tolerances for printing DIN ISO 2768-m
- Machining radii min. R1, further on request
- Web: www.phoenixcontact.com

Additional Information:
A. Attachment point for the optional PCB
B. Pivot bearing HINGED COVER
C. Locking HINGED COVER
D. Notch for locking release, by screw driver
E. Exposed side
F. Inner side
G. Recommended PCB outline on
www.phoenixcontact.com webcode: #0512
H. Mounting rail like EN 60715, TH 35-7.5 or
mounting rail similar to EN 60715, TH 35-15x1.5