



Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent has been obtained from the manufacturer. All rights are reserved in case of patent, utility model or design patent registrations.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Alle Rechte vorbehalten, in dem Fall der Patent-, Gebrauchsmuster- oder Designschutzrechte.


HOUSING LEFT




HOUSING RIGHT




FRONT PLATE




HINGED COVER





FOOT CATCH
2:1



SPRING
5:1



Assembly example: ME MAX 22,5 F G 3-3



General Information:

- Simplified representation, exemplary shown in gray.
- Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2.
- PA plastic parts with about 2% (% by weight) moisture content.
- Workpiece zero point for mechanical processing
- Tolerances for mechanical processing are ISO 2768-mk
- Tolerances for printing DIN ISO 2768-m
- Machining radii min. R1, further on request
- Web: www.phoenixcontact.com

Additional Information:

A. Attachment point for the optional PCB

B. Pivot bearing HINGED COVER

C. Locking HINGED COVER

D. Notch for locking release, by screw driver

E. Exposed side

F. Inner side

G. Recommended PCB outline on www.phoenixcontact.com webcode: #0512

H. Mounting rail like EN 60715: TH 35-7,5 or mounting rail TH 35-15x1,5 similar to EN 60715

KIT			
Pos.	QTY	Description	Material
1	1	HOUSING LEFT	PA
2	1	HOUSING RIGHT	PA
3	1	FRONT PLATE	PA
4	1	HINGED COVER	PC
5	1	FOOT CATCH	STL
6	1	SPRING	STL