








Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Bauartbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.



Recommended PCB



General Information:

- Simplified representation, exemplary shown in black
- Tolerances, apply in a normal climate according to DIN EN ISO 291-23/50-2, PA plastic parts with about 2% (% by weight) moisture content.
- When using this connection technology in housing systems from Phoenix Contact see the appropriate documentation.
- Restricted area
- Suction surface
- Zero part
- General tolerances PCB:
 - dimensions ≤ 30 : $\pm 0,1/R \pm 0,2/\pm 1^\circ$
 - dimensions > 30 : $\pm 0,15/R \pm 0,2/\pm 1^\circ$
 - symmetry: 0,2
- Document excluded from change process
- Web: www.phoenixcontact.com

Additional Information

A. PCB $t=1,6 \pm 0,2$

Pos.	QTY	Description	Material
1	1	HOUSING	PA
2	4	SOLDER PIN	Cu alloy

DIN A3	document-no. / ri 00810417 / 04	article-no. 2697204	scale 2:1	- Simplified representation - Document excluded from change process - Linear dimensions [mm]
	date 09.02.2023	document-type		
page 1 of 1	description MSTBO 2,5/ 4-G1R THRR44 BK			