







Transfer or duplication of this document as well as the utilisation or communication of its content are not permitted unless express consent is granted. Violations give rise to claims for damages. All rights reserved in case of patent, utility model or design patent registrations. Tolerance specifications do not include clearances inherent in the design.

Weitergabe sowie Vervielfältigung dieses Dokuments, Verwertung und Mitteilung seines Inhalts sind verboten, soweit nicht ausdrücklich gestattet. Zuwiderhandlungen verpflichten zu Schadenersatz. Alle Rechte für den Fall der Patent-, Gebrauchsmuster- oder Designeintragung vorbehalten. Bauartbedingtes Spiel ist in den Toleranzangaben nicht berücksichtigt.





HOUSING UPPER PART



- General Information:
- Simplified representation, exemplary shown in gray.
 - Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2
 - Workpiece zero point for mechanical processing
 - Tolerances for mechanical processing are ISO 2768-mK
 - Tolerances for printing DIN ISO 2768-m
 - Machining radii min. R1, further on request
 - Web: www.phoenixcontact.com

Assembly example


Overall dimensions compliant DIN 43880



- Additional Information:
- A. Housing lower part
 - B. Mounting rail like EN 60715: TH 35-7,5 or mounting rail TH 35-15x1,5 similar to EN 60715
 - C. Cover
 - D. PCB 1 (main PCB)
 - E. Position PCB 9 or position plate
 - F. Header for HBUS (PSTD 0,65X0,65/9-2,54)
 - G. PCB guidance for PCB 11

Pos.		QTY	Description		Material		
1		1	HOUSING UPPER PART		PC		
			DIN A2	document-no. / ri 00908955 / 02	article-no. 2896047	scale 1:1	- Simplified representation - Document excluded from change process - Linear dimensions [mm]
			date 04.02.2025	document-type TECDOC 2D_Productdrawing			
			description BC 35,6 OT U22 KMGY				
			page 1 of 2				

Marking area




General Information:

- Tolerances apply in a normal climate according to DIN EN ISO 291-23/50-2
- Workpiece zero point for mechanical processing
- Tolerances for mechanical processing are ISO 2768-mK
- Tolerances for printing DIN ISO 2768-m
- Machining radii min. R1, further on request
- Web: www.phoenixcontact.com

Additional information:

- A) Max. marking area left and right for pad printing and laser printing
The marking area has 2mm distance from all contours of this face

 DIN A4		document-no. / ri 00908955 / 02		article-no. 2896047		scale 1:1		- Simplified representation - Document excluded from change process - Linear dimensions [mm]
		date 04.02.2025		document-type TECDOC 2D_Productdrawing				
		description BC 35,6 OT U22 KMGY						
page 2		of 2						